



2.5.4 RESISTENCIAS CONFORMABLES

TIPO	LONG	ZONA INACTIVA	POTENCIA
Ø4	400	90	200
	550	90	315
	750	90	400
	950	90	500
	1150	90	630
	1350	90	750
	1650	90	1000
	2000	90	1250
	2500	90	1500



Ø3 X 3	200	90	175
	240	90	175
	300	90	225
	350	90	250
	390	90	215
	400	90	300
	450	90	350
	500	90	400
	540	90	325
	600	90	500
	650	90	400
	700	90	470
	740	90	500
	800	90	600
	900	90	610
	940	90	630
	1000	90	700
	1140	90	750
	1200	90	800
	1500	90	900
	1800	90	1100
	2000	90	1400
Ø2,2x4,2	200	90	175
	250	90	190
	330	90	200
	380	90	225
	430	90	250
	480	90	300
	560	90	350
	630	90	400
	700	90	450
	750	90	550
	860	90	625
	950	90	675
	1000	90	700
	1200	90	800
	1400	90	950
	1600	90	1100
	1800	90	1200
	2000	90	1300



Ø5x7	210	90	200
	250	90	250
	300	90	300
	400	90	400
	500	90	500
	600	90	600
	700	90	650
	800	90	750
	900	90	850
	1000	90	950
	1250	90	1100
	1500	90	1250
	1750	90	1600
	2000	90	1750
	2500	90	1850
	3000	90	2000
Ø6x6	210	90	200
	250	90	250
	300	90	300
	400	90	400
	500	90	500
	600	90	600
	700	90	650
	800	90	750
	900	90	850
	1000	90	950
	1250	90	1100
	1500	90	1250
	1750	90	1600
	2000	90	1750
	2500	90	1850
	3000	90	2000